

Product images	Application	Characteristic	Structure
	► Transportation of food liquids	► Smooth inner and outer walls	► Color: Transparent with yellow wide stripes
	► Delivery of beverages with an alcohol concentration of less than 20%	► Good liquidity	► Temperature:-10/+60°C
	► Agricultural water supply and irrigation	► Good airtightness	► Standard:
	► Food factory	► Good UV resistance	Compliant with the US FDA Food Contact Safety Standards
		► Good resistance to ozone	Compliant with the EU 10/2011 Food Contact Material Standard
► Hose wall: environmentally friendly PVC		► Resistant to aging, hydrolysis, and mold	
► Reinforcement: Spiral steel wire+polyester fiber woven mesh			

Part Number	Internal Diameter	Wall thickness	Weight	Work pressure	Burst pressure	Bursting Pressure	Coil Length
	mm	mm	g/m	bar	bar	bar	m
933C-010-100	10	3.0	200	12	36	0.7	100
933C-012-100	12	3.0	250	12	36	0.7	100
933C-016-100	16	3.0	300	12	36	0.7	100
933C-019-50	19	3.0	400	12	36	0.7	50
933C-025-50	25	3.5	600	13	39	0.7	50
933C-032-50	32	4.0	800	13	39	0.6	50
933C-038-50	38	4.5	1,000	13	39	0.6	50
933C-050-50	50	5.0	1,400	15	45	0.6	50
933C-060-50	60	5.0	1,800	15	45	0.5	50
933C-064-40	64	5.0	2,000	15	45	0.5	40
933C-075-40	75	5.0	2,200	15	45	0.5	40

Note: * All technical parameters are approximate values and measured under conditions of 23 °C operating temperature and 50% ambient humidity. They may change accordingly based on actual operating conditions.

* We will periodically revise or adjust the relevant parameters. If we are unable to notify in a timely manner, please forgive us and refer to the data published on the website or company.