

Single layer laminated platinum sulfide silicone hose

Product images	Application	Characteristic	Structure
	► Transport of liquids	► Corrosion preventive	► Color: Translucent
	► Extraction of air/steam	► Smooth inner wall	► Temperature: -40/+220°C
	► CIP and SIP cleaning	► Odorless/Odorless	► Length can be customized
	► Food factory	► Good liquidity	
	► Medical equipment	► Good airtightness	
	► Cosmetics industry	► High temperature and steam resistance	
	► Hose wall: FDA certified food grade silicone	► Reinforcement: Single layer polyester fabric	► FDA certification

Part Number	Internal diameter mm	Outer diameter mm	Wall thickness mm	Weight kg/m	Burst pressure bar	Bending radius mm	Coil length m
ZS08-003-100	3.18	9.53	3.175	0.088	≥38	35	6
ZS08-005-100	4.76	11.73	3.500	0.120	≥38	35	6
ZS08-006-100	6.35	12.70	3.200	0.132	≥35	30	6
ZS08-009-100	9.53	15.88	3.200	0.176	≥35	30	6
ZS08-012-100	12.77	22.22	4.700	0.345	≥25	80	6
ZS08-016-100	15.88	25.15	4.600	0.400	≥23	85	6
ZS08-019-100	19.05	28.58	4.800	0.480	≥23	110	6
ZS08-022-100	22.23	32.00	4.900	0.550	≥13	115	6
ZS08-025-100	25.40	35.69	5.100	0.650	≥13	140	6

Note: * All technical parameters are approximate values and measured under conditions of 23 °C operating temperature and 50% ambient humidity. They may change accordingly based on actual operating conditions.

* We will periodically revise or adjust the relevant parameters. If we are unable to notify in a timely manner, please forgive us and refer to the data published on the website or company.