

Double layer cloth, single layer steel wire reinforced platinum sulfide silicone hose

Product images	Application	Characteristic	Structure
	► Transport of liquids	► Corrosion resistance	► Color: Red
	► Extraction of air/steam	► Smooth inner wall	► Temperature: -60/+220 °C
	► CIP and SIP cleaning	► Odorless/Odorless	Instant high temperature resistance +260 °C
	► Food factory	► Good liquidity	
	► Medical devices	► Good airtightness	
	► Hose wall: FDA certified food grade silicone	► Cosmetics industry	► High temperature and steam resistance
	► Reinforcement: Double layer small mesh polyester woven fabric	► Flame retardant	
	Single layer steel wire spiral reinforcement	► FDA certification	

Part Number	Internal Diameter	Wall thickness	Coil Length
	mm	mm	m
ZS14-038-4	38	4.5 (+0.8/-0.8)	4
ZS14-045-4	45	4.5 (+0.8/-0.8)	4
ZS14-051-4	51	4.5 (+0.8/-0.8)	4
ZS14-057-4	57	4.5 (+0.8/-0.8)	4
ZS14-063-4	63	4.5 (+0.8/-0.8)	4
ZS14-076-4	76	4.5 (+0.8/-0.8)	4
ZS14-089-4	89	4.5 (+0.8/-0.8)	4
ZS14-102-4	102	4.5 (+0.8/-0.8)	4
ZS14-114-4	114	4.5 (+0.8/-0.8)	4
ZS14-120-4	120	4.5 (+0.8/-0.8)	4
ZS14-127-4	127	4.5 (+0.8/-0.8)	4
ZS14-152-4	152	4.5 (+0.8/-0.8)	4

Note: * All technical parameters are approximate values and measured under conditions of 23 °C operating temperature and 50% ambient humidity. They may change accordingly based on actual operating conditions.

* We will periodically revise or adjust the relevant parameters. If we are unable to notify in a timely manner, please forgive us and refer to the data published on the website or company.